


### 6x19+AT

Funi per gru - argani - paranchi - imbracature - Steel wire rope for crane - electric hoist - slings



**COSTRUZIONE:** 6x19 warrington  
+ A.T. (6/6 + 6 + 1)  
**RESISTENZA:** 1770 N/mm<sup>2</sup> (180 Kg/mm<sup>2</sup>)  
e 1960 N/mm<sup>2</sup> (200 Kg/mm<sup>2</sup>)


**CONSTRUCTION:** 6x19 warrington  
+ FC (6/6 + 6 + 1)  
**TENSILE GRADE:** 1770 N/mm<sup>2</sup> (180 Kg/mm<sup>2</sup>)  
and 1960 N/mm<sup>2</sup> (200 Kg/mm<sup>2</sup>)

Diametro Diameter	Peso / 100 m Weight / 100 m	Carico di rottura minimo garantito Minimum breaking load guaranteed			
		1770 N/mm <sup>2</sup> kN	180 Kg/mm <sup>2</sup> kg	1960 N/mm <sup>2</sup> kN	200 Kg/mm <sup>2</sup> Kg
3	3,4	4,9	500	-	-
4	5,3	9,07	925	-	-
5	8,9	13,7	1.400	17,6	1.800
6	11,4	22,1	2.250	25,5	2.600
7	17,1	29,4	3.000	33,3	3.400
8	21,0	39,2	4.000	43,2	4.400
9	28,2	51,5	5.250	57,4	5.850
10	31,6	63,7	6.500	70,3	7.170
11	40,3	78,5	8.000	85,5	8.720
12	45,4	86,8	8.850	101,0	10.300
13	54,3	103	10.500	-	-
14	65,1	118	12.000	-	-
16	80,8	151	15.400	-	-
18	117,0	176	17.950	-	-
20	126,0	218	22.230	-	-
22	164,9	263	26.820	-	-
24	188,9	311	31.700	-	-

Dati disponibili su richiesta  
Dates available upon request

### SV636AT

Funi per gru - argani - paranchi - imbracature - Steel wire rope for crane - electric hoist - slings



**COSTRUZIONE:** 6x36 WS  
+ A.T. (14 + 7/7 + 7 + 1)  
**RESISTENZA:** 1770 N/mm<sup>2</sup> (180 Kg/mm<sup>2</sup>)

**CONSTRUCTION:** 6x36 WS  
+ FC (14 + 7/7 + 7 + 1)  
**TENSILE GRADE:** 1770 N/mm<sup>2</sup> (180 Kg/mm<sup>2</sup>)

Diametro Diameter	Peso / 100 m Weight / 100 m	Carico di rottura minimo garantito Minimum breaking load guaranteed	
		1770 N/mm <sup>2</sup> kN	180 Kg/mm <sup>2</sup> Kg
8	23,0	37,4	3.820
9	29,5	47,3	4.820
10	36,0	58,4	5.960
11	43,2	70,7	7.210
12	52,0	84,1	8.580
13	60,6	98,7	10.060
14	68,9	114,0	11.620
15	79,5	131,0	13.350
16	90,0	150,0	15.290
18	113,0	189,0	19.260
19	132,0	211,0	21.510
20	147,0	234,0	23.850
22	173,0	283,0	28.840
24	207,0	336,0	34.240
26	242,0	395,0	40.260
28	276,0	458,0	46.680
29	296,0	491,0	50.040
30	318,0	526,0	53.600
32	361,0	598,0	60.940
34	409,0	675,0	68.790
36	456,0	757,0	77.140
38	510,0	843,0	85.910
40	569,0	935,0	95.280
42	631,0	1.030,0	104.960