


SV19CT

Fune per gru a torre - autogru - *Steel wire rope for tower cranes - mobile telescopic cranes*

COSTRUZIONE: SV 19 CT compattata,
antigirevole
RESISTENZA: 1960 N/mm² (220 Kg/mm²)
- 2160 N/mm² (200 Kg/mm²)
QUALITÀ DISPONIBILE: lucida, ingrassata,
zincata

CONSTRUCTION: SV 19 CT compact,
non-rotating
RESISTANCE: 1960 N/mm² (220 Kg/mm²)
- 2160 N/mm² (200 Kg/mm²)
AVAILABLE QUALITY: bright, galvanized

Diametro Diameter	Peso / metro Weight / meter	Carico di rottura minimo garantito Minimum breaking load guaranteed			
		1960 N/mm ² kN	200 Kg/mm ² Kg	2160 N/mm ² kN	220 Kg/mm ² Kg
8	0,31	53,3	5.440	59	6.020
9	0,39	67,6	6.890	74,5	7.590
10	0,48	83,5	8.500	93	9.480
11	0,58	100,9	10.290	110,3	11.250
12	0,69	120	12.240	132	13.460
13	0,79	141	14.380	155	15.800
14	0,94	163,4	16.660	181	18.450
15	1,06	188	19.170	210,5	21.450
16	1,22	213,4	21.760	236	24.060
18	1,55	270,1	27.540	298	30.390