


SV35 FLEXO

Fune per gru navali - gru a torre - Steel wire rope for marine crane - tower cranes



COSTRUZIONE: 35x7 antigirevole  
 RESISTENZA: 1960 N/mm<sup>2</sup> (200 kg/mm<sup>2</sup>)  
 QUALITÀ: zincata lubrificata

CONSTRUCTION: 35x7 non-rotating rope  
 TENSILE GRADE: 1960 N/mm<sup>2</sup> (200 Kg/mm<sup>2</sup>)  
 QUALITY AVAILABLE: galvanised lubricated

Diametro Diameter	Peso / 100 m Weight / 100 m	Carico di rottura minimo garantito Minimum breaking load guaranteed	
		1960 N/mm <sup>2</sup> kN	200 Kg/mm <sup>2</sup> Kg
8	27,3	47,0	4.790
10	42,7	73,5	7.490
11	52,0	88,9	9.060
12	62,5	106,0	10.810
13	73,0	124,0	12.640
14	84,7	144,0	14.480
15	96,6	165,0	16.820
16	110,0	188,0	19.160
17	123,0	212,0	21.610
18	139,0	238,0	24.260
19	154,0	265,0	27.010
20	171,0	294,0	28.960
22	207,0	356,0	36.280
24	250,0	423,0	43.110
25	265,1	459,0	46.780
26	292,1	497,0	50.650
28	339,0	576,0	58.700
30	386,0	662,0	67.460
32	440,1	753,0	76.740
34	494,0	850,0	86.620
36	553,1	953,0	97.120
38	614,0	1.060	108.020