


SV636

Fune per gru - paranchi - carriponte - argani - impieghi diversi - Steel wire rope for electric hoist - crane - different applications



**COSTRUZIONE:** 6x36 WS  
+ A.M. (14 + 7/7 + 7 + 1)  
**RESISTENZA:** 1770 N/mm<sup>2</sup> (180 Kg/mm<sup>2</sup>),  
1960 N/mm<sup>2</sup> (200 Kg/mm<sup>2</sup>) e  
2160 N/mm<sup>2</sup> (220 Kg/mm<sup>2</sup>)

**CONSTRUCTION:** 6x36 WS  
+ IWRC (14 + 7/7 + 7 + 1)  
**TENSILE GRADE:** 1770 N/mm<sup>2</sup> (180 Kg/mm<sup>2</sup>)  
and 1960 N/mm<sup>2</sup> (200 Kg/mm<sup>2</sup>)  
and 2160 N/mm<sup>2</sup> (220 Kg/mm<sup>2</sup>)

Diametro Diameter	Peso / 100 m Weight / 100 m	Carico di rottura minimo garantito Minimum breaking load guaranteed		
		1770 N/mm <sup>2</sup> kN	1960 N/mm <sup>2</sup> kN	2160 N/mm <sup>2</sup> kN
mm	[Kg]			
8	26,2	40,3	44,7	49,2
9	33,1	51,0	56,5	62,3
10	40,9	63,0	69,8	76,9
11	49,5	76,2	84,4	93,0
12	58,9	90,7	100,0	110,0
13	69,1	106,0	118,0	130,0
14	80,2	124,0	137,0	151,0
15	89,9	142,0	-	186,0
16	105,0	161,0	179,0	197,0
18	133,0	204,0	226,0	249,0
19	149,0	227,0	-	278,0
20	164,0	252,0	279,0	308,0
22	198,0	305,0	338,0	372,0
24	236,0	363,0	402,0	433,0
26	276,0	426,0	472,0	520,0
28	321,0	494,0	547,0	603,0
29	335,0	530,0	-	-
30	360,0	567,0	-	690,0
32	419,0	645,0	715,0	787,0
34	462,0	728,0	-	-
36	530,0	817,0	904,0	997,0
38	578,0	910,0	-	-
40	654,0	1.010	1.120	1.230
42	712,0	1.110	-	-
44	792,0	1.220	1.350	1.490
48	942,0	1.450	1.610	1.770
51	1.031	1.640	-	-
52	1.110	1.700	1.890	2.080
56	1.280	1.980	2.190	2.410
58	1.341	2.120	-	-
60	1.470	2.270	2.510	2.770
64	1.730	2.334	2.687	2.952
67	1.900	2.560	2.933	3.237
71	2.080	2.795	3.266	3.531
77	2.470	3.296	3.816	4.169
83	2.900	3.816	4.385	4.836
96	3.870	4.954	5.738	6.278
103	4.400	5.581	6.523	7.063