







## Tiranti ed imbragature in fune d'acciaio con anima metallica — Multi legs steel wire rope sling with steel core

TIPO AG / AG TYPE					TIPO AN 2 G / AN 2 G TYPE				
Fune diametro Rope diameter	Codice Code	Portata WLL	Campanella Superiore Master link	Gancio Hook	Codice Code	Portata WLL	Campanella Superiore Master link	Gancio Hook	
									
mm	no.	Kg	mm	mm	no.	Kg	mm	mm	
8	HFAZ1GC08A	750	120x60x13	20	HFAZ2GC08A	1.050	750	120x60x13	
10	HFAZ1GC10A	1.150	120x60x13	24	HFAZ2GC10A	1.600	1.150	120x60x13	
12	HFAZ1GC12A	1.700	120x60x13	30	HFAZ2GC12A	2.300	1.700	120x60x13	
14	HFAZ1GC14A	2.250	120x60x13	30	HFAZ2GC14A	3.150	2.250	160x90x17	
16	HFAZ1GC16A	3.000	160x90x17	30	HFAZ2GC16A	4.200	3.000	160x90x19	
18	HFAZ1GC18A	3.700	160x90x17	38	HFAZ2GC18A	5.200	3.700	160x90x19	
20	HFAZ1GC20A	4.600	160x90x19	38	HFAZ2GC20A	6.500	4.600	180x100x22	
22	HFAZ1GC22A	5.650	160x90x19	50	HFAZ2GC22A	7.800	5.650	180x100x22	
24	HFAZ1GC24A	6.700	180x100x22	50	HFAZ2GC24A	9.400	6.700	210x115x25	
26	HFAZ1GC26A	7.800	180x100x22	56	HFAZ2GC26A	11.000	7.800	210x115x25	
28	HFAZ1GC28A	9.000	210x115x25	56	HFAZ2GC28A	12.500	9.000	275x145x28	
30	HFAZ1GC30A	10.400	210x115x25	80	HFAZ2GC30A	14.700	10.400	275x145x32	
32	HFAZ1GC32A	11.800	275x145x28	80	HFAZ2GC32A	16.500	11.800	285x155x36	
36	HFAZ1GC36A	15.000	285x155x36	80	HFAZ2GC36A	21.000	15.000	285x155x36	
40	HFAZ1GC40A	18.500	285x155x36	88	HFAZ2GC40A	26.000	18.500	270x140x40	


Tolleranze diverse da quelle previste dalla Normativa Vigente devono essere richieste in Sede di ordine. Portate secondo norma EN 13414-1.

**Coefficiente di sicurezza: 5**


Tolerances that are different from the ones established by the regulations in force must be requested at the time of order. Capacity as per EN 13414-1 regulation.

**Safety Factor: 5**

## Tiranti ed imbragature in fune d'acciaio con anima metallica — Multi legs steel wire rope sling with steel core



TIPO AN 3 G 10 / AN 3 G 10 TYPE



TIPO AN 4 G / AN 4 G TYPE

Fune diametro Rope diameter	Codice Code	Portata WLL		Campanella superiore Master link	Campanella inferiore Transition link	Gancio Hook	Codice Code	Portata WLL		Campanella superiore Master link	Campanella inferiore Transition link	Gancio Hook
		$\beta=45^\circ \alpha=90^\circ$	$\beta=60^\circ \alpha=120^\circ$	$\beta=45^\circ \alpha=90^\circ$	$\beta=60^\circ \alpha=120^\circ$			$\beta=45^\circ \alpha=90^\circ$	$\beta=60^\circ \alpha=120^\circ$			
mm	no.	Kg	Kg	mm	mm	mm	no.	Kg	Kg	mm	mm	mm
8	HFAZ3GC08A	1.550	1.100	120x60x13	120x60x13	20	HFAZ4GC08A	1.550	1.100	120x60x13	120x60x13	20
10	HFAZ3GC10A	2.400	1.700	160x90x17	120x60x13	22	HFAZ4GC10A	2.400	1.700	160x90x17	120x60x13	22
12	HFAZ3GC12A	3.550	2.500	160x90x17	120x60x13	24	HFAZ4GC12A	3.550	2.500	160x90x17	120x60x13	24
14	HFAZ3GC14A	4.800	3.400	180x100x22	160x90x17	26	HFAZ4GC14A	4.800	3.400	180x100x22	160x90x17	26
16	HFAZ3GC16A	6.300	4.500	180x100x22	160x90x17	30	HFAZ4GC16A	6.300	4.500	180x100x22	160x90x17	30
18	HFAZ3GC18A	7.800	5.650	180x100x22	160x90x19	30	HFAZ4GC18A	7.800	5.650	180x100x22	160x90x19	30
20	HFAZ3GC20A	9.800	6.900	275x145x28	180x100x22	38	HFAZ4GC20A	9.800	6.900	275x145x28	180x100x22	38
22	HFAZ3GC22A	11.800	8.400	275x145x28	180x100x22	38	HFAZ4GC22A	11.800	8.400	275x145x28	180x100x22	38
24	HFAZ3GC24A	14.000	10.000	275x145x28	180x100x22	50	HFAZ4GC24A	14.000	10.000	275x145x28	180x100x22	50
26	HFAZ3GC26A	16.500	11.500	275x145x32	210x115x25	50	HFAZ4GC26A	16.500	11.500	275x145x32	210x115x25	50
28	HFAZ3GC28A	19.000	13.500	285x155x36	190x110x28	50	HFAZ4GC28A	19.000	13.500	285x155x36	190x110x28	50
30	HFAZ3GC30A	25.000	15.600	270x140x40	275x145x32	56	HFAZ4GC30A	25.000	15.600	270x140x40	275x145x32	56
32	HFAZ3GC32A	31.500	17.500	340x180x45	285x155x36	80	HFAZ4GC32A	31.500	17.500	340x180x45	285x155x36	80
36	HFAZ3GC36A	39.000	22.500	390x215x51	270x140x40	80	HFAZ4GC36A	39.000	22.500	390x215x51	270x140x40	80
40	HFAZ3GC40A	47.000	28.000	406x203x55	390x215x51	88	HFAZ4GC40A	47.000	28.000	406x203x55	390x215x51	88

Tolleranze diverse da quelle previste dalla Normativa Vigente devono essere richieste in Sede di ordine. Portate secondo norma EN 13414-1.

**Coefficiente di sicurezza: 5**

Tolerances that are different from the ones established by the regulations in force must be requested at the time of order. Capacity as per EN 13414-1 regulation.

**Safety Factor: 5**